

Item NO.	Specification	Approx. AWG Iqurv.	Square (mm ²)	Approx. Weight (kg/km)		Carriers	Total No. of Individ. Ends	Single Directory (mm)	Approx. Flat Width (mm)	Approx. Thickness (mm)	Approx. Resistance (Ohm/km)
4T012-0101	B17/10/0.12T*8P	15.5	1.92	18.84		17	170	0.12	5.0	0.7	9.2
4T012-2041	B16/4/0.12T*8P	19.5	0.72	7.09		16	64	0.12	1.9	0.7	24.6
4T012-2061	B16/6/0.12T*8P	17.0	1.09	10.64		16	96	0.12	2.6	0.8	16.4
4T012-3051	B24/5/0.12T*8P	16.0	1.36	13.30		24	120	0.12	3.3	0.8	13.1
4T012-3061	B24/6/0.12T*8P	15.0	1.63	15.96		24	144	0.12	3.8	0.8	10.9
4T012-3071	B24/7/0.12T*8P	14.5	1.90	18.62		24	168	0.12	4.0	1.2	9.4
4T012-3081	B24/8/0.12T*8P	14.0	2.17	21.28		24	192	0.12	6.6	0.8	8.2
4T012-3111	B24/11/0.12T*6P	13.5	2.99	29.26		24	264	0.12	5.5	1.2	6.0
4T012-3141	B24/14/0.12T*5P	12.5	3.80	37.25		24	336	0.12	8.0	0.6	4.7
4T012-6061	B48/6/0.12T*6P	12.0	3.26	31.92		48	288	0.12	9.0	0.7	5.5
4T012-6101	B48/10/0.12T*6P	10.0	5.43	53.21		48	480	0.12	12.0	1.0	3.3
4T012-6111	B48/11/0.12T*6P	10.5	5.97	58.53		48	528	0.12	11.3	1.0	3.0
4T012-6151	B48/15/0.12T*6P	8.0	8.14	79.81		48	720	0.12	16.0	1.3	2.2
4T012-6161	B48/16/0.12T*7P	8.0	8.69	85.13		48	768	0.12	19.0	1.4	2.0
4T012-6181	B48/18/0.12T*6P	7.0	9.77	95.77		48	864	0.12	16.0	1.4	1.8
4T012-6191	B48/19/0.12T*5.5P	7.0	10.31	101.09		48	912	0.12	21.0	0.8	1.7
4T012-6261	B48/26/0.12T*6P	6.5	14.11	138.34		48	1248	0.12	20.0	1.6	1.3
4T016-3051	B24/5/0.16T*13P	14.0	2.41	23.65		24	120	0.16	5.3	1.1	7.4
4T016-3061	B24/6/0.16T*5P	13.0	2.90	28.38		24	144	0.16	5.6	1.2	6.1
4T016-3081	B24/8/0.16T*8P	13.5	3.86	37.84		24	192	0.16	6.7	1.6	4.6
4T016-3101	B24/10/0.16T*8P	11.5	4.83	47.30		24	240	0.16	8.0	1.6	3.7
4T016-3121	B24/12/0.16T*7P	10.5	5.79	56.75		24	288	0.16	8.5	1.7	3.1
4T018-3041	B24/4/0.18T*6P	14.5	2.44	23.94		24	96	0.18	4.6	1.1	7.3
4T018-3081	B24/8/0.18T*8P	11.5	4.89	47.89		24	192	0.18	8.5	1.6	3.6
4T018-3101	B24/10/0.18T*8P	10.5	6.11	59.86		24	240	0.18	9.0	1.7	2.9
4T018-6041	B48/4/0.18T*6P	11.5	4.89	47.89		48	192	0.18	15.0	0.5	3.6
4T020-6181	B48/18/0.2T*2.5P	3.0	27.14	266.04		48	864	0.2	25.0	2.6	0.7
4T025-3041	B24/4/0.25T*6P	11.5	4.71	46.19		24	96	0.25	6.9	1.6	3.8
4T025-6101	B48/10/0.25T*3.5P	4.5	23.56	230.94		48	480	0.25	26.5	2.3	0.8
4T025-6161	B48/16/0.25T*3P	2.5	37.70	369.50		48	768	0.25	32.0	1.4	0.5
4TA36-6081	B48/8/0.127T*8.5P	11.5	4.86	47.68		48	384	0.127	10.0	0.8	3.7
4TA36-6191	B48/19/0.127T*6P	7.5	11.55	113.23		48	912	0.127	16.4	1.7	1.5